



### Bilge Pump Cable

#### Premium Tinned Copper

Color conductors: black, brown and red  
Insulation: grey

- Conductors specifically for bilge pumps
- Oil resistant
- SJTOW-A water resistant jacket

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
<b>16/3 AWG (3x1 mm<sup>2</sup>)</b>			
100'	156610	.348"	78 lbs
250'	156625	8.85 mm	35.5 kg
<b>14/3 AWG (3x2 mm<sup>2</sup>)</b>			
100'	156410	.377"	99 lbs
250'	156425	9.6 mm	45.0 kg
500'	156450		



### Flat Ribbon Bonded RGB Cable

#### Tinned Copper

Conductor colors: red, light blue, green, and white

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
<b>18/4 AWG (4x0.08 mm<sup>2</sup>)</b>			
100'	160010	3/32"x3/8"	48 lbs
1000'	160099	2.3x9.3 mm	21.8 kg
<b>16/4 AWG (4x1 mm<sup>2</sup>)</b>			
100'	160110	1/8"x15/32"	64 lbs
1000'	160199	2.6x10.5 mm	29.0 kg
<b>14/4 AWG (4x2 mm<sup>2</sup>)</b>			
100'	160210	7/64"x15/32"	92 lbs
1000'	160299	3.0x11.9 mm	41.7 kg



### Super Flex Audio Cable

#### Premium Tinned Copper

- Super flexible, easy to run
- Clear jacket to blend into the environment
- Drawn copper, unidirectional lay for ultimate in sound quality
- Tinned copper for corrosion resistance in the marine environment

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
<b>18/2 AWG (2x0.8 mm<sup>2</sup>)</b>			
100'	142810	.265"	29 lbs
		6.7 mm	13 kg
<b>16/2 AWG (2x1 mm<sup>2</sup>)</b>			
100'	142610	.319"	51 lbs
250'	142625	8.1 mm	23.1 kg
500'	142650		
<b>14/2 AWG (2x2 mm<sup>2</sup>)</b>			
100'	142410	.345"	65 lbs
250'	142425	8.8 mm	29.5 kg
1000'	142499		



### RGB + Speaker Cable

#### Tinned Copper

18 AWG conductors for RGB lighting: yellow, red, blue, green

16 AWG conductors for speaker connections: black and red

- Saves time by running only one cable
- Meets ABYC standards

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
<b>18/4 AWG (4x0.08 mm<sup>2</sup>) + 16/2 AWG (2x1 mm<sup>2</sup>)</b>			
25'	170002		
100'	170010	.352"	69.9 lbs
		8.9 mm	31.7 kg
250'	170025		



### GTO 15 High Voltage Cable (15000V)

Color conductors: white

- Coupler output to antenna

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
<b>14 AWG (2 mm<sup>2</sup>)</b>			
25'	150102	1/4"	38 lbs
100'	150110	6.4 mm	17.2 kg

