

2655 Napa Valley Corp. Dr., Napa, CA 94558
(707) 226-8600 FAX: (707) 226-9670
Date: March, 1997 Rev: 00

Inlet, Non-metallic
30A 125V

Catalog Number: 301EL-B

- Item: Inlet, non-metallic locking
- Rating: 30 amperes, 125 volts
- Materials: Cap & Bezel are glass-filled polyester.
Plug body is nylon with CTI greater than 600 volts.
Contact blades and terminal parts are nickel plated brass.
Rear enclosure is glass-filled polyester with UL flammability rating of 94V-0.
- Terminals: Clamp-type terminals. No. 10 terminal screws accept up to 8 AWG wire.
- Enclosure: Provided. Has integral strain relief for oval jacketed cable.
- Blades: Blades are solid brass 0.060" thick.
- Mounting Screws: Not provided. No. 8 panhead recommended. Mounting holes are 0.16" diameter on a 2.43" square pattern.
- Mounting Gasket: Solid Neoprene, 1/8" thick.
- Cap Closure: Pressure close. Provided with Easy Lock™ bayonet style locking system. Provides weather seal when used with cords having threaded, or Easy Lock™, sealing rings.
- Listings: UL Marine listed, File E57672
CSA certified, File LR81290
Complies with ABYC and Coast Guard Standards.

Dimensions:

