



RC9190 track profile



Dominic & Steve Randall, International Cadet

- ✓ Spring-loaded plunger stops allow fast, positive positioning of track slides.
- ✓ Slides are available with swivelling cleat and fairlead to suit different crewing positions.
- ✓ RC91942 features a small camcleat and fairlead and suits line sizes 2-8mm (3/32-5/16").
- ✓ RC91941 RopeGlide™ ring has a 'soft' attachment which allows up to 250° rotation.
- ✓ Dinghy and small catamaran jib sheet leads.
- ✓ Adjustable hiking strap systems.
- ✓ Dinghy outhauls.
- ✓ Alloy track.
- ✓ Glass fibre reinforced nylon slides.
- ✓ Grade 316 stainless steel fixtures.

TRACK FASTENINGS – 4mm (5/32") countersunk fasteners at 75mm (2 15/16") centres. **STOP HOLES** – 19mm (3/4") centres

PRODUCT No.	DESCRIPTION	LENGTH mm	M.W.L. kg	B.L. kg	WEIGHT g	LENGTH in	M.W.L. lb	B.L. lb	WEIGHT oz
Series 19									
RC9190-0.3	Track	296	-	-	64	11 5/8	-	-	2.3
RC9190-0.45	Track	446	-	-	96	17 9/16	-	-	3.4
RC9190-1.5	Track	1496	-	-	321	58 7/8	-	-	11.3
RC9190-3.0	Track	2996	-	-	643	117 5/16	-	-	22.7
RC91901	Slide, saddle	57	220	440	26	2 1/4	485	970	0.9
RC91940	Slide, saddle, plunger stop	71	220	440	33	2 13/16	485	970	1.2
RC91941	Slide, soft-attached ring, plunger stop	71	100	200	28	2 13/16	220	440	1.0
RC91942	Slide, swivelling fairlead & cleat, plunger stop	71	100*	200*	115	2 13/16	220*	440*	4.1
RC91944	Slide, saddle with ferrule eye, plunger stop	71	220	440	40	2 13/16	485	970	1.4
RC91980	Track end, plastic (2 pack)	19	-	-	2	3/4	-	-	0.1

*Line load through cleat